

# YOMEL

La más amplia y versatil línea de desmalezadoras  
*The widest and most versatile line of rotary cutters*



Desmalezadoras Hileradora **HM 302 - HM 302** Rotary cutters-Windrower

# Desmalezadoras Hileradora **HM 302**

## **HM 302** Rotary cutters-Windrower



Para el trabajo se eleva la rueda de transporte quedando la máquina apoyada en las dos ruedas traseras y en la barra de tiro del tractor. Esto le brinda mayor estabilidad absorbiendo mejor las imperfecciones del terreno, lograndose así un mejor corte.

*To work transport wheel rises, the machine being supported in the two rear wheels and the bar draft of the tractor. This gives more stability better absorbing the imperfections of the land, thus achieving a better cut.*

Desmalezadora-Hileradora de forrajes y malezas de 3 mts de ancho de labor, con cuchillas oscilantes rotativas y rastrillo contenedor de malezas. Con tercer rueda para transporte accionada por circuito hidráulico.

*Rotary cutter-Windrower of forages and weeds of 3 mts working width, with oscillating rotary blades and weed rake container. With a third wheel to transport operated by hydraulic circuit.*

Transmisión mediante correa plana, para ser accionada por toma de fuerza a 540 rpm. Control remoto desde el tractor para regular altura de corte desde 0 a 0.45 m., con cilindros y mangueras. *Transmission through flat belt, to be driven by take-off at 540 rpm.*

*Remote control from the tractor to regulate cutting height from 0 to 0.45 meters, with cylinders and hoses.*



Registro de nivelación.  
Leveling record.



Regulación de cuchillas.  
Blade regulation.

### CARACTERISTICAS TECNICAS - TECHNICAL FEATURES

#### MODELO HM 302

Acople de tractor	Lateral
Ancho de labor	3 m
Pot. máx. admitida en TDF	80 HP
RPM toma de fuerza	540
Peso aproximado	1085 Kg
Rodados (con neumáticos)	(3) 600x16
Rendimiento aprox. por Ha/h:	2.5
Altura de corte	0/450 mm
Transmisión	Correa plana 5x9600
Caja de mando	Engranajes cónicos
En posición de trabajo	
Ancho	4.675 m
Largo	3.314 m
En Transporte	
Ancho	1.945 m
Largo	5.475 m
Transmisión	Arbol cardánico y correa plana
Posición de trabajo	Tercer rueda en posición de transporte

#### HM 302 MODEL

Tractor Hitch	Lateral
Working width	3 m
Maximum admitted power in PTO	80 HP
RPM PTO	540
Approximate weight	1085 Kg
Wheels (with tires)	(3) 600x16
Approximate yield by Ha/h:	2.5
Cutting height	0/450 mm
Transmission	Flat belt 5x9600
Control box	Bevel gear
In working position	
Width	4.675 m
Length	3.314 m
In Transport	
Width	1.945 m
Length	5.475 m
Transmission	Shaft transmission and flat belt
Working position	Third wheel in transport position