

YOMEL

La más amplia y versatil línea de desmalezadoras
The widest and most versatile line of rotary cutters



Desmalezadoras línea liviana **LT** - Light line rotary cutters **LT**

Desmalezadoras línea liviana LT

Light line rotary cutters LT



1321 LT



Sistema de regulación de altura de corte mediante registro mecánico, opcional hidráulico, para control remoto del tractor.
Regulation system of cutting height by means of mechanical record, optional, hydraulic, from tractor command.



1020-1021 LT



1320-1321 LT



1510-1520-1521 LT

Sistema de corte con cuchillas oscilantes de acero forjadas, templadas y revenidas.
Cutting system with oscillating, reversible, and forged blades; high wear resistance steel.



1021-1321 LT



1521 LT

Rueda de apoyo trasera de hierro, altura regulable.
Rear iron support wheel, regulated height.



Caja de transmisión para servicio pesado y barra cardánica protegida por un zafe de discos ajustables que acciona al existir sobrecargas.

Transmission box for heavy duty and transmission shaft protected by automatic safeguard of adjustable discs that works when overloads occur.

CARACTERISTICAS TECNICAS - TECHNICAL FEATURES

MODELO / MODEL	1510 LT	1520 LT	1521 LT	1320 LT	1321 LT	1020 LT	1021 LT
Ancho de labor / Working width	1.50m	1.50m	1.50m	1.30 m	1.30 m	1 m	1 m
Potencia máx. en PTO / Maximum PTO power	40 HP	40 HP	40 HP	40 HP	40 HP	40 HP	40 HP
Enganche	Arrastre Central	3 P. Central	3 P. Central	3 P. Central	3 P. Central	3 P. Central	3 P. Central
Hitch	Central trail	3-point Central	3-point Central	3-point Central	3-point Central	3-point Central	3-point Central
RPM toma de fuerza / Tractor RPM	540	540	540	540	540	540	540
Altura de corte / Cutting height	0.05/0.45 m	0.05/0.45 m	0.05/0.45 m	0.05/0.45 m	0.05/0.45 m	0.05/0.45 m	0.05/0.45 m
Rodados	2 (500x15)	Rueda de apoyo	Rueda de apoyo	Rueda de apoyo
Tyres	2 (500x15)	Support wheel	Support wheel	Support wheel
Reg. altura de corte / Cutting height range	Mecánica* / Mechanic*	3 Puntos / 3-point	3 Puntos / 3-point	3 Puntos / 3-point	3 Puntos / 3-point	3 Puntos / 3-point	3 Puntos / 3-point
Peso aproximado / Approximate weight	284kg	221kg	251kg	180 kg	210 kg	150 kg	180 kg

* Opcional hidráulica / Hydraulic optional*



Casa Central: RUTA 65 y Av. MITRE - Tel.: +54-2317-430776 Fax: +54-2317-430749 - (6500) 9 DE JULIO - Bs. As. - Argentina - ventas@yomel.com.ar - web: www.yomel.com.ar